

new ARCHIBAR SL200/WB (White Balance)



art. 15182

Short description

The ARCHIBAR SL200/WB it has the same shape and design of the ARCHIBAR SL300 but with less powerful LEDs. Suitable for applications where the object to lit isn't higher than 15 meters.

ARCHIBAR SL200/WB (white balance) is equipped with LEDs with different wavelenghts in order to vary the color temperature of the light from 2900K up to 6000K

Light source with 30 powerful LEDs.

Available in 4 different measures

- Standard 90 cm. (15 lenses)
- On request 60 - 120 - 150 cm
- Standard fixture colour finishing is grey. Optional black and white (art. FX-COLOUR).

Description

Specifications are subject to change:

- SOURCE (n. 15 LEDs)

n. 15 (2900K) warm white LEDs

n. 15 (6000K) cool white LEDs

Total out lumen: 9000lm

new ARCHIBAR SL200/WB (White Balance)

Total light power: 90W

- OPTIC

25°; standard (38 mm lenses)

On request: narrow, wide (38 mm lenses)

- TILT

Manual 160°;

- CONTROL

Standard interface: RS-485

Protocol: USITT DMX 512

- CONNECTIONS

Signal: 4pin IP 67 connector (male-female)

Available as accessories:

- Wireless DMX receiver

Main Power: 3pin IP 67 connector (male-female)

- SAFETY

n. 2 eyebolts for safety chains

- SETUP AND CONFIGURATION

Control panel with touch technology and led display with flip function

or by DRS (remote control device)

Dedicated DMX channel for white balance

DMX or Auto mode with Master-Slave function

Intelligent temperature control

Halogen simulation

CYM simulation

Flicker-free function

Smooth dimming function

- IP 67 RATING PROTECTION

- POWER SUPPLY

Voltage range: 100-240VAC

new ARCHIBAR SL200/WB (White Balance)

Frequency range: 47-63Hz

Active Power factor:

PF>0.94/230VAC, PF>0.98/120VAC

Current:

0.60A@230VAC

Power: 100W

Fuse T4A (inside fixture)

• PHYSICAL

WxDxH: 928 x110x93 mm (dimension of profile)

Weight: 6 Kg.