



art. 1304
CITYBEAM LED24 RGBW/FC

Studio Due

emotion and creativity in light



CitybeamLED²⁴

RGBW/FC Full color

- 5° narrow beam angle
- Astonishing level of brightness up to 250 meters
 - High Power RGBW/FC 20W LEDs
 - Energy efficient

To reach impressive heights, no matter how complex it is, the new CITYBEAM LED 24 is the right solution. Whatever is the final application, where long distance light output is required the CITYBEAM LED family solve your problem.

Standard fixture colour finishing is black, optional grey and white.

TECHNICAL FEATURES

• SOURCE

n. 24 RGBW (20W) LEDs
288W total light power

• OPTIC

5° (45 mm lenses)

On request:

- medium, wide 45 mm lenses

• TILT Manual 160°

• CONTROL

Standard interface: RS-485, optocoupled input

Protocol: USITT DMX512

• CONNECTIONS

Signal: 4pin IP 67 Amphenol connector (male-female)

Main Power: 3x1mm cable

Available as accessories:

- Wireless DMX receiver

• SAFETY

n. 2 eyebolts for safety chains

• SETUP AND CONFIGURATION

Control panel with touch technology

Led display with flip function

Dedicated DMX channel for white balance

DMX or Auto mode with Master-Slave function

Intelligent temperature control

Flicker-free function

Smooth dimming function

Halogen simulation

CYM simulation

• RATING PROTECTION

IP 67

• DMX CHANNELS

- 9CH mode

- 5CH mode

- 4CH mode

• POWER SUPPLY

Voltage range: 88-264VAC, 124-370VDC

Frequency range: 47-63Hz

Active Power factor:

PF>0.95/230VAC, PF>0.98/115VAC

Current: 1.1A@230VAC; Fuse T5A

Power: 300W (all color full power)

• PHYSICAL

WxDxH: 615x185x420 mm

Weight: 18,5 Kg.



Click on the QR Code with your smartphone to go directly to the fixture website page

Studio Due

emotion and creativity in light

PHYSICAL



© Copyright 2014 Studio Due light srl
Strada Poggino, 100
01100 Viterbo (Italy)
tel. +39.0761.352520 (4 lines)
fax +39.0761.352653
C.F. e P. IVA 05793121004

Specifications are subject to change without notice. Trademarks are the property of Studio Due Light Srl
www.studiodue.com